

P/N MS24693-S226

Military-Fasteners.com

### Description

Fastener Length: 3/8", Thread: 6-40, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

1	S	2	4	6	9	3	S	2	2	6	5

SKU / Model:	MS24693S226
Minimum Qty (MOQ):	100
NSN:	5305-00-411-0696
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS24693-S226 Specifications

Thread Class:	2a				
Thread Direction:	Right-hand				
Thread Length:	0.234 Inches Minimum And 0.315 Inches Maximum				
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum				
Head Style:	Flat Countersunk				
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum				
Internal Drive Style:	Cross Recess Type 1				
Nominal Thread Diameter:	0.138 Inches				
Thread Quantity Per Inch:	40				
Minimum Tensile Strength:	60000 Pounds Per Square Inch				
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum				
Screw Material:	Steel				
Screw Material Document And Classification:	Astm A108 Comp 1010 Assn Std Single Material Response				
Screw Surface Treatment:	Cadmium And Chromate				
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses				
Thread Series Designator:	Unf				
Nondefinitive Spec/std Data:	3 Type Or 3c Style				
Departure From Cited Designator:	As Modified By Matl				

# How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS24693-S226</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.