

## Description

length: 3/16in., thread: 6-32 countersunk, countersunk flat head, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[MS24693S23](#)

SKU / Model:	MS24693S23
Minimum Qty (MOQ):	100
NSN:	5305-00-773-2695
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS24693-S23 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.126 Inches Minimum And 0.188 Inches Maximum
<b>Fastener Length:</b>	0.156 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.238 Inches Minimum And 0.279 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 1010 Or Steel
<b>Screw Material Document And Classification:</b>	Qq-s-630 Fed Spec 1st Material Response Or Qq-s-631 Fed Spec 1st Material Response Or Qq-s-634 Fed Spec 1st Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 3 Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.