

Description

Fastener Length: 5/16", Thread: 8-36, Thread Length: 15/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS24693S247](#)

SKU / Model:	MS24693S247
Minimum Qty (MOQ):	100
NSN:	5305-00-053-8548
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS24693-S247 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.163 Inches Minimum And 0.240 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type Or 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S247> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.