

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693S32](#)

SKU / Model:	MS24693S32
Minimum Qty (MOQ):	100
NSN:	5305-00-174-0711
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-S32 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.887 Inches Minimum And 0.949 Inches Maximum
Fastener Length:	1.000 Inches Minimum And 1.124 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Aircraft, Stratolifter C-135; Aircraft, F-16; Aircraft, Awacs, E-3a
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Departure From Cited Designator:	As Modified By Fastener Lg

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.