

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693S322
Minimum Qty (MOQ):	40 EA
NSN:	5305-00-267-9679
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS24693-S322 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.167 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.556 Inches Minimum And 0.635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec Single Material Response Or Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-b-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S322> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.