

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693S33](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24693S33 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-051-7341 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24693-S33 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.063 Inches Minimum And 1.125 Inches Maximum |
| Fastener Length: | 1.125 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.238 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 1010 Or Steel |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 1st Material Response Or Qq-s-631 Fed Spec 1st Material Response Or Qq-s-634 Fed Spec 1st Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.