

Description

anodized aluminum - length: 7/8", thread: 8-32, 100°, countersunk - flat head - machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693A53
Minimum Qty (MOQ):	10
NSN:	5305-01-295-4053
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N MS24693A53 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.772 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Ty 1 Cl 1 Or Ty 2 Cl 1 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693A53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.