

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693-B2](#)

| | |
|-------------------------|--|
| SKU / Model: | MS24693B2 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-141-6504 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N MS24693B2 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.120 Inches Minimum And 0.201 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.191 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Copper Alloy |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693B2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.