



Military-Fasteners.com

P/N MS24693B50

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693B50
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-141-6523
Schedule B:	7415.33.8050
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS24693B50 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.335 Inches Minimum And 0.428 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 270 Or Copper Alloy 274 Or Copper Alloy 360
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693B50> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.