

## P/N MS24693BB273

## **Description**

length: 5/8", thread: 10-32, countersunk, flat head, black brass, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS24693BB273

Minimum Qty (MOQ): 100

NSN: 5305-00-225-6213

Schedule B: 7415.39.0000

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









# P/N MS24693BB273 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.480 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Helicopter, Utility/search And Recovery Uh-1n; Helicopter, Green Giant H-3; Missile, Minuteman Lgm-30; T1a Aircraft; Aircraft, Hercules C-130f; Aircraft, Hercules Kc-130; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Advance Attack, Ah-1w; Aircraft, C-18a, Ec-18b
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693BB273">https://military-fasteners.com/screws/machine+screws/MS24693BB273</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.