

## P/N MS24693BB274

## **Description**

length: 3/4", thread: 10-32, black brass, countersunk, flat head

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS24693BB274

Minimum Qty (MOQ): 100

NSN: 5305-00-957-2385

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24693BB274 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf

# **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693BB274">https://military-fasteners.com/screws/machine+screws/MS24693BB274</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693BB274">https://military-fasteners.com/screws/machine+screws/MS24693BB274</a> and selecting the quantity you