

**Description**

length: 5/16", thread: 4-40, black brass, countersunk, flat head

\* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

**Additional Information**

**Alternate Part Numbers**

[MS24693-BB3](#)

SKU / Model:	MS24693BB3
Minimum Qty (MOQ):	100
NSN:	5305-00-842-5297
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N MS24693BB3 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.231 Inches Minimum And 0.281 Inches Maximum
<b>Fastener Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.191 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 270 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 764 Or Copper Alloy 770
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693BB3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.