

P/N MS24693BB3

Description

length: 5/16", thread: 4-40, black brass, countersunk, flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693-BB3

SKU / Model: MS24693BB3


Minimum Qty (MOQ): 100


NSN: 5305-00-842-5297

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









P/N MS24693BB3 Specifications

Thursd Class.	2-
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.231 Inches Minimum And 0.281 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 270 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 764 Or Copper Alloy 770
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693BB3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.