

P/N MS24693BB30

Description

black brass - length: 3/4", thread: 6-32, countersunk, flat head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS24693BB30

Minimum Qty (MOQ): 100

NSN: 5305-00-929-6554


ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









^{*} See page 2 for technical characteristics

P/N MS24693BB30 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693BB30 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.