

Description

black brass - length: 2", thread: 6-32, 100°, countersunk - flat head - machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS24693BB40 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-088-0259 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |



* See page 2 for technical characteristics

P/N MS24693BB40 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.816 Inches Minimum And 1.940 Inches Maximum |
| Fastener Length: | 1.938 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.238 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Surface Treatment: | Oxide |
| Screw Surface Treatment Document And Classification: | Mil-c-13924 Class 4 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693BB40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.