

P/N MS24693BB5

Description

black brass, length: 7/16", thread: 4-40, countersunk, flat head, machine screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS24693BB5

Minimum Qty (MOQ): 100

NSN: 5305-00-842-5302

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper









^{*} See page 2 for technical characteristics

P/N MS24693BB5 Specifications

| Thread Class: | 2a |
|------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.356 Inches Minimum And 0.406 Inches Maximum |
| Fastener Length: | 0.406 Inches Minimum And 0.438 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.191 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 270 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 764 Or Copper Alloy 770 |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693BB5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24693BB5 and selecting the quantity you