

**Description**

length: 3/4", thread: 8-32, black brass, countersunk, flat head, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24693-BB52](#)

SKU / Model:	MS24693BB52
Minimum Qty (MOQ):	100
NSN:	5305-00-957-2387
Schedule B:	7415.33.8010
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



\* See page 2 for technical characteristics

## P/N MS24693BB52 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.688 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.285 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693BB52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.