

Description

black brass - length: 1-1/8", thread: 8-32, 100°, countersunk - flat head - machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693BB55
Minimum Qty (MOQ):	50
NSN:	5305-00-226-7922
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS24693BB55 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.125 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693BB55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.