

Description

Fastener Length: 1/2", Thread: 10-24, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693BB72
Minimum Qty (MOQ):	45 EA
NSN:	5305-00-225-3846
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N MS24693BB72 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.355 Inches Minimum
Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Helicopter, Utility/search And Recovery Uh-1n; Aircraft, (ac-130h, Mc130h, Ec-130e, Hc-130)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 268 Or Copper Alloy 270
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693BB72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.