



★ FASTENERS

Military-Fasteners.com

P/N MS24693C10

Description

length: 1", thread: 4-40, 18-8 stainless steel, 70,000 psi tensile strength, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693-C10](#)

SKU / Model:	MS24693C10
Minimum Qty (MOQ):	100
NSN:	5305-00-921-3349
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693C10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.919 Inches Minimum And 0.969 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.