

Description

Length: 1-1/4", thread: 1/4-20, flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS24693-C100](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24693C100 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-450-3141 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693C100 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.078 Inches Minimum And 1.140 Inches Maximum |
| Fastener Length: | 1.188 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.442 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 85000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C100> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.