

Description

MS24693C204 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693-C204](#)

SKU / Model:	MS24693C204
Minimum Qty (MOQ):	100
NSN:	5305-01-174-5379
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24693C204 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.226 Inches Nominal
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 100.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf
Specification/standard Data:	96906-ms24693c204 Government Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C204> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.