

Description

Length: 1/2", Thread: 10-32, flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

NAS1351C3-32 MS24693-C272

SKU / Model:	MS24693C272
Minimum Qty (MOQ):	100
NSN:	5305-00-051-0227
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693C272 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C272> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.