

**Description**

corrosion resistant steel, length: 3/8", thread: 1/4-28, countersunk, flat head, machine screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24693C292
Minimum Qty (MOQ):	100
NSN:	5305-00-724-7845
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N MS24693C292 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.304 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.442 Inches Minimum And 0.507 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C292> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.