

## P/N MS24693C297

## **Description**

MS24693C297 Machine Screw

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS24693-C297

SKU / Model: MS24693C297

Minimum Qty (MOQ): 25

NSN: 5305-01-318-2148

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24693C297 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.663 Inches Minimum And 0.765 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 3c Style

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693C297">https://military-fasteners.com/screws/machine+screws/MS24693C297</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693C297">https://military-fasteners.com/screws/machine+screws/MS24693C297</a> and selecting the quantity you