



★ FASTENERS

Military-Fasteners.com

P/N MS24693C298

## Description

Length 1", thread 1/4-28, countersunk flat head, corrosion resistant steel, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[MS24693-C298](#)

SKU / Model:	MS24693C298
Minimum Qty (MOQ):	50
NSN:	5305-00-725-5911
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS24693C298 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.929 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C298> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.