

P/N MS24693C300

Military-Fasteners.com

Description

length: 1-1/4, thread: 1/4-28, countersunk, corrosion resistant steel, flat head, MS24693 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693-C300

| SKU / Model: | MS24693C300 |
|-------------------------|---|
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-725-5913 |
| Schedule B: | 7318.15.9000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693C300 Specifications

| Thread Class: | 2a |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 1.179 Inches Minimum And 1.250 Inches Maximum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.442 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS24693C300</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.