

## P/N MS24693C302

### **Description**

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 1-1/2", fine thread, flat countersunk, MS24693 series screw

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

MS24693-C302

SKU / Model: MS24693C302

Minimum Qty (MOQ): 50

NSN: 5305-00-725-5917

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24693C302 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.429 Inches Minimum And 1.500 Inches Maximum
Fastener Length:	1.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693C302">https://military-fasteners.com/screws/machine+screws/MS24693C302</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693C302">https://military-fasteners.com/screws/machine+screws/MS24693C302</a> and selecting the quantity you