

Description

MS24693C304 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693-C304](#)

SKU / Model:	MS24693C304
Minimum Qty (MOQ):	50
NSN:	5305-00-459-9838
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693C304 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.507 Inches Minimum And 1.640 Inches Maximum
Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting Or Steel
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C304> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.