

Description

Fastener Length: 2-1/2", Thread: 6-32, Thread Length: 2-13/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693-C42](#)

SKU / Model:	MS24693C42
Minimum Qty (MOQ):	25
NSN:	5305-00-903-2197
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS24693C42 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.344 Inches Minimum And 2.406 Inches Maximum
Fastener Length:	2.406 Inches Minimum And 2.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693C42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.