

## P/N MS24693C55

### **Description**

length: 1-1/8", thread: 8-32, corrosion resistant steel, countersunk, flat head

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

MS24693-C55

SKU / Model: MS24693C55

Minimum Qty (MOQ): 100

NSN: 5305-00-902-2137

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS24693C55 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.125 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693C55">https://military-fasteners.com/screws/machine+screws/MS24693C55</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693C55">https://military-fasteners.com/screws/machine+screws/MS24693C55</a> and selecting the quantity you