

Description

Fastener Length: 5/8", Thread: 6-32, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693NB29
Minimum Qty (MOQ):	130 EA
NSN:	5305-00-009-1784
Schedule B:	7415.33.8050
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS24693NB29 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.534 Inches Minimum And 0.565 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Screw Surface Treatment:	Nickel
Screw Surface Treatment Document And Classification:	Qq-n-290 Ty5 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693NB29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.