



★ FASTENERS

Military-Fasteners.com

P/N MS24693S277

Description

length: 1-1/8", thread: 10-32, countersunk, flat head, cadmium plated carbon steel, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[MS24693-S277](#)

SKU / Model:	MS24693S277
Minimum Qty (MOQ):	100
NSN:	5305-00-957-7813
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693S277 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.125 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693S277> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.