

Description

cadmium plated carbon steel, length: 1-1/2", thread: 10-32, countersunk, flat head, machine screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**MS24693-S280

SKU / Model:	MS24693S280
Minimum Qty (MOQ):	100
NSN:	5305-00-958-6374
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693S280 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Fastener Length:	1.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec Single Material Response Or Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693S280> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.