

Description

length: 1-1/4, thread: 1/4-28, countersunk, flat head, cadmium plated carbon steel, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS24693S300 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-733-3042 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS24693S300 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.179 Inches Minimum And 1.250 Inches Maximum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.442 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec Single Material Response Or Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693S300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.