

Description

length: 1-1/4", thread: 6-32, countersunk, flat head, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693-S34](#)

SKU / Model:	MS24693S34
Minimum Qty (MOQ):	100
NSN:	5305-00-930-1577
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693S34 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.128 Inches Minimum And 1.190 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693S34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.