

P/N MS24693S5

Description

length: 7/16", thread: 4-40, countersunk, flat head, cadmium plated carbon steel, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693-S5

SKU / Model: MS24693S5


Minimum Qty (MOQ): 100

NSN: 5305-00-959-4743

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24693S5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.388 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel
Screw Material Document And Classification:	Qq-s-630 Fed Spec 1st Material Response Or Qq-s-631 Fed Spec 1st Material Response Or Qq-s-634 Fed Spec 1st Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693S5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.