

Description

length: 3", thread: 8-32, countersunk, flat head, cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS24693S66 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-160-9515 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS24693S66 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.750 Inches Minimum |
| Fastener Length: | 2.906 Inches Minimum And 3.000 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.285 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 100.0 Degrees Maximum |
| Screw Material: | Steel Comp 1013 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1017 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1021 Or Steel Comp 1022 Or Steel Comp 1524 Or Steel Comp 1025 Or Steel Comp 1527 Or Steel Comp 1030 Or Steel Comp 1033 Or Steel Comp 1034 Or Steel Comp 1035 Or Steel Comp 1038 Or Steel Comp 1040 Or Steel Comp 1541 Or Steel Comp 1108 Or Steel Comp 1109 Or Steel Comp 1110 |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693S66> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.