

P/N MS24693S95

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS24693S95

Minimum Qty (MOQ): 100

NSN: 5305-00-781-5653

Schedule B: 7318.15.4000

ECCN: FAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24693S95 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.525 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec Single Material Response Or Qq-s-631 Fed Spec Single Material Response Or Qq-s-634 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693S95 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24693S95 and selecting the quantity you