

**Description**

Fastener Length: 3-23/64", Thread: 1/4-28, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24694A135
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-291-3988
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS24694A135 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.515 Inches Minimum And 0.547 Inches Maximum
Fastener Length:	3.015 Inches Minimum And 3.362 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.447 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Or Qq-a-225 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Tyi Or Tyii Mil Spec Single Treatment Response
Thread Series Designator:	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694A135> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.