

## Description

anodized aluminum - length: 17/32", grip: 3/32", thread: 8-32, 100°, countersunk - flat head - machine screw - structural

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS24694A5
Minimum Qty (MOQ):	10
NSN:	5305-01-488-8925



# P/N MS24694A5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.203 Inches Minimum And 0.281 Inches Maximum
Fastener Length:	0.531 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.283 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Hawkeye
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Or Qq-a-225,t4 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625,type 1 Or 2 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.