

Description

Fastener Length: 31/32", Thread: 10-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24694A57
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-225-4595
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N MS24694A57 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	0.969 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694A57> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.