

Description

Fastener Length: 5/8", Thread: 8-32, Thread Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS24694A6 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-068-7045 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N MS24694A6 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.344 Inches Minimum And 0.484 Inches Maximum |
| Fastener Length: | 0.578 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.283 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response Or Qq-a-430 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.