



Military-Fasteners.com

P/N MS24694A8

Description

Fastener Length: 23/32", Thread: 8-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS24694A8           |
| Minimum Qty (MOQ):      | 5 EA                |
| NSN:                    | 5305-00-068-7047    |
| Schedule B:             | 7616.10.9090        |
| ECCN:                   | 9A991               |
| National Motor Freight: | 013680, Alum Screws |



\* See page 2 for technical characteristics

# P/N MS24694A8 Specifications

|                           |  |
|---------------------------|--|
| Thread Class:             | 3a   |
| Thread Direction:         | Right-hand                                     |
| Thread Length:            | 0.376 Inches Minimum                           |
| Fastener Length:          | 0.719 Inches Nominal                           |
| Head Style:               | Flat Countersunk                               |
| Head Diameter:            | 0.283 Inches Minimum And 0.332 Inches Maximum  |
| Internal Drive Style:     | Cross Recess Type 1                            |
| Nominal Thread Diameter:  | 0.164 Inches                                   |
| Thread Quantity Per Inch: | 32   |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch                   |
| Countersink Angle:        | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material:           | Aluminum Alloy 2024                            |
| Screw Surface Treatment:  | Anodize  |
| Thread Series Designator: | Unc  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.