

**Description**

Fastener Length: 1-3/32", Thread: 1/4-28, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24694-C104](#)

SKU / Model:	MS24694C104
Minimum Qty (MOQ):	25
NSN:	5305-00-054-9243
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS24694C104 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.461 Inches Minimum
Fastener Length:	1.094 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.447 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C104> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.