

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 37/64", flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24694-C107](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24694C107 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-054-9246 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24694C107 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.499 Inches Minimum And 0.578 Inches Maximum |
| Fastener Length: | 1.265 Inches Minimum And 1.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.491 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 85000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 100.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 309 Or Steel Comp 310 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347 |
| Screw Material Document And Classification: | Qq-s-763 Fed Spec All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C107> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.