

Description

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 37/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**MS24694-C111

SKU / Model:	MS24694C111
Minimum Qty (MOQ):	25
NSN:	5305-00-057-0476
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24694C111 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.499 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	1.515 Inches Minimum And 1.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.447 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-s-763,series 300 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Material To Be Equal To Or Interchangeable With 16-18 Or 18-8 Chromium Nickel Alloy Steel Which Meets Min Ts Or 85,000 Psi
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C111> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.