

**Description**

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 37/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24694-C111](#)

SKU / Model:	MS24694C111
Minimum Qty (MOQ):	25
NSN:	5305-00-057-0476
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N MS24694C111 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.499 Inches Minimum And 0.578 Inches Maximum
<b>Fastener Length:</b>	1.515 Inches Minimum And 1.562 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.447 Inches Minimum And 0.507 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	85000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-s-763,series 300 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Special Features:</b>	Material To Be Equal To Or Interchangeable With 16-18 Or 18-8 Chromium Nickel Alloy Steel Which Meets Min Ts Or 85,000 Psi
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C111> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.