

Description

Length: 25/32", grip: 5/16", thread: 10-32, countersunk, flat head, structural, corrosion resistant steel, MS24694

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24694-C54](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24694C54 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-824-2021 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24694C54 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.376 Inches Minimum And 0.516 Inches Maximum |
| Fastener Length: | 0.766 Inches Minimum And 0.812 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.327 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 85000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 304 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C54> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.