

P/N MS24694C55

Description

Corrosion resistant steel length: 27/32", grip: 3/8", thread: 10-32, countersunk, flat head, machine screw, structural

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24694-C55

SKU / Model: MS24694C55

Minimum Qty (MOQ): 100

NSN: 5305-00-824-2028

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24694C55 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.828 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24694C55 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.